

M5 & M10 End Fittings



NH34034-4
2" Flat Hook
Breaking Strength: 6,000 lbs.
Working Load Limit: 2,000 lbs.



NH43024-1
2" Flat Hook
Breaking Strength: 10,000 lbs.
Working Load Limit: 3,333 lbs.



NH34024-1
2" Flat Delta Ring
Breaking Strength: 5,000 lbs.
Working Load Limit: 1,670 lbs.



NH34024-9
2" Flat Delta Ring
Breaking Strength: 10,000 lbs.
Working Load Limit: 3,333 lbs.



NH8029-1
2" Heavy-duty Spring Loaded E Fitting
Breaking Strength: 4,500 lbs.
Working Load Limit: 1,500 lbs.



NH7900-1
2" Flat Snap Hook
Breaking Strength: 6,000 lbs.
Working Load Limit: 2,000 lbs.



NH1000-6
2" Wire-Formed Closed Hook
Breaking Strength: 10,000 lbs.
Working Load Limit: 3,333 lbs.



NH1000-7
2" Wire-Formed Closed Hook
Breaking Strength: 5,000 lbs.
Working Load Limit: 1,667 lbs.



NH12007
2" Twisted Snap Hook
Breaking Strength: 5,000 lbs.
Working Load Limit: 1,667 lbs.



NH34025-14
1-3/4" D Ring
Breaking Strength: 5,000 lbs.
Working Load Limit: 1,667 lbs.

NH12009
2" Flat Snap Hook
Breaking Strength: 10,000 lbs.
Working Load Limit: 3,333 lbs.



Sewn Eye
Please consult factory for breaking strength and working load limit. Call for best pricing.



NH7936-1
2" Slotted Delta Ring, CHP rated
Breaking Strength: 16,200 lbs.
Working Load Limit: 5,400 lbs.



NH7915-1
4" Flat Hook, CHP rated
Breaking Strength: 15,000 lbs.
Working Load Limit: 5,000 lbs.



NH10008
2" Wire Form Hook
Breaking Strength: 15,000 lbs.
Working Load Limit: 5,000 lbs.



NH7270-1
3/8" Grab Hook
Breaking Strength: 16,200 lbs.
Working Load Limit: 5,400 lbs.



NH1211
2" Forged Snap Hook
Breaking Strength: 10,000 lbs.
Working Load Limit: 3,333 lbs.



NH7270-18
18" Chain Anchor, CHP rated
Breaking Strength: 16,200 lbs.
Working Load Limit: 5,400 lbs.



NH33210
2" Hook & Keeper
Breaking Strength: 5,000 lbs.
Working Load Limit: 1,667 lbs.



NH7445-1
4" V Ring, CHP rated
Breaking Strength: 20,000 lbs.
Working Load Limit: 5,000 lbs.



			QTY	1-19	20-49	50-99	100+
NH38034-4	2" Flat Hook			4.20	3.95	3.75	3.50
NH34024-1	2" Flat Delta Ring, Stamped			2.80	2.60	2.50	2.40
NH8029-1	2" Spring Loaded E Fitting	Heavy-Duty		2.80	2.60	2.50	2.40
NH1000-6	2" Wire-Formed Closed Hook			4.25	3.95	3.60	3.40
NH12007	2" Twisted Snap Hook			5.00	4.40	4.05	3.85
NH43024-1	2" Flat Hook			4.60	4.25	4.10	3.95
NH34024-9	2" Flat Delta Ring			3.55	3.30	3.05	2.80
NH7900-1	2" Flat Snap Hook			4.15	3.75	3.60	3.50
NH1000-7	2" Wire-Formed Closed Hook			3.75	3.55	3.30	2.95
NH34025-14	1-3/4" D ring			2.80	2.60	2.50	2.40

			QTY	1-19	20-49	50-99	100+
NH12009	2" Flat Snap Hook			8.15	7.40	6.85	6.40
NH7936-1	2" Slotted Delta Ring			3.50	3.15	2.95	2.80
NH1000-8	2" Wire Form Hook			6.60	6.00	5.65	5.40
NH1211	2" Forged Snap Hook			7.80	7.50	7.10	6.70
NH33210	2" Hook & Keeper			6.80	6.25	5.80	5.50
NH12012	2" Twisted Hook			8.80	8.40	8.05	7.80
End Fittings 15M 16M							
NH7915-1	4" Flat Hook			6.95	6.15	5.85	5.55
NH7270-1	3/8" Grab Hook			12.10	11.00	10.75	10.25
NH7270-18	18" Chain anchor with hook, CHP rated			20.15	19.15	18.25	17.65
NH7445-1	4" V Ring, CHP rated			8.40	7.60	7.20	6.75

An assembly is rated at the lowest minimum working load limit of any of its components. Component selections will affect overall ratings of the assembly.

An assembly is rated at the lowest minimum working load limit of any of its components. Component selections will affect overall ratings of the assembly.